

Manufactured by Hydro Tek 2353 Almond Avenue Redlands, CA 92374 Ph 800.274.9376 Fax 909.799.9888 www.hydrotek.us



The *RPFE1 (PFE)* is your solution to EPA local and state regulations mandating wastewater containment, filtration and reuse. Designed as an addition to your wash pad, the 6-stage filtration process includes a 3-tank oil-water-solids separation system, oil coalescing, multi-stage filtration process, and an on-demand water delivery system. Maintenance is simple, just clean or change the cartridges as indicated by the pressure gauge. This is the system of choice to recycle pit wastewater at rental centers, vehicle maintenance facilities, and detail and body shops.

PROCESS FLOW RATE	Wastewater process flow up to 6gpm	
FRAME	Stainless Steel	
POWER REQUIREMENTS	120 Volt AC, 20-amp	
	SEPARATOR TANK	
FRAME	Stainless steel frame and panels	
OIL SEPARATION	Center water column removal Process, 1 cu ft oil coalescing spheres, dual oil absorption	
	media bags	
SOLIDS SEPARATION	3 stage inclined gravity separation with sludge / solids drain	
	FILTRATION	
TRANSFER PUMP	6.0gpm, centrifugal and automatic level control	
PUMP POWER	115-volt / 9.4 amp, panel controlled	
BAG FILTERS	1) 100 micron polyester felt bag 7" x 32"	
PRIMARY FILTER	135 sq ft cellular media pleated, 1) 20 micron	
SECONDARY	1) 4.5" x 20" polyester pleated, 10 micron	
CARBON FILTER	1) 4.5" x 20" activated carbon: hydro carbon, oil and odor removal	
FINAL FILTRATION	1) 5 micron polyester felt bag 7" x 32"	
SANITATION	Automatic chlorinator injection system	
	WATER DELIVERY & STORAGE	
WATER DELIVERY PUMP	6.0gpm 45psi, centrifugal jet w/ automatic on-demand operation, 115-volt, 9.4 amp	
SAFETY CONTROL	Automatic low level safety pump shut-off system	

185 gallon polyethylene tank w/ automatic make up fill valve, 29" x 47" x 30"

One Year accessory warranty

40" x 48" x 58", 427# dry weight, (demo and deliver with standard pickup truck)

## Featuring...

WARRANTY

STORAGE TANK

**DIMENSIONS / WEIGHT** 

- ✓ Reuse wastewater: Separate sediment and oil and filter water to be reused by your pressure washer
- ✓ Compact and simple to install: Plug into standard power outlet, connect hoses to integrated storage tank, power on and use – Plug and play in less than an hour.
- ✓ Simple to operate and maintain: Includes automatic pump controls, sump pump, low water shut-off switch and replenishment valve. Clean or replace filter cartridges when indicated and pull quick purge valves.
- ✓ Low cost wastewater compliance for medium to light duty, non-detergent washing
- ✓ Rust proof stainless steel construction

TO:	
COMMENTS:	
YOUR PRICE:	
DISTRIBUTED BY:	

